DIGITAL FO				CO	CATEGORY PAG			PAGE 1	
							[:	S]	OF 3
						Ŋ	IUMBER:	63XMX-S00	2
the VAX	6000	series		s containi		_		on early sh	-
personr	nel to	access	the int	erior of	syste	m cabir	et. Emb	ot permit u edded stora abinet fron	ge controls
	_			Front door					ess only to
QUICK (CHECK:	Front	door sho	ould have	openi	ng for	embedde	d storage.	
PRE/COREQUISITE FCO: N/A					MTTI HRS 1 hour 				
TOOL/TE	EST EQU	JIPMENT	: Fi	ield Servi	ice To	ol Kit			1
				FCO PAR	RTS IN	FORMATI	ON		
FCO KIT NO. DESCRIPTION OF CONTENTS EQ KIT VARIA					VARIATION CABILITY				
<u>:</u>									
		_i		FCO CHARG	GING I	NFORMAT	ION	İ	
WARRA	 \NTY/C(ONTRACT			NONW	ARRANTY	/NONCON	TRACT	
							- CIME MAMEDIAI ONLY		
ON-SITE OF		OF F	-SITE 	ON-SITE		OFF-SITE 		MATERIAL ONLY	
TRAVEL/ INSTALL	EQ KIT	 INSTAL	EQ L KIT	TRAVEL/ INSTALL		 INSTAI	EQ L KIT	ORDER-ADMI	N,HANDLING NG & EQ KIT
DEC	DEC	DEC	_ DEC		 N/A 	N/A	N/A	N/A	
CSSE FSHQ LO			OGISTICS Ewing			FS PRODUCT SAFETY Bob Brister 			
Jan Sicard on mult:			cument is published iple media including , Customer Services			FCO RELEASE DATE 15 November 1989			
MICROMEDIA Mic Diane MacDonald Cus			Microfic Customer	iche Libraries, er Services CD-ROM and crofiche Libraries.			FCO REVISION A		

POPULATION	PARTS AVAILABILITY
12	15 November 1989

	FCO 63XMX-S00	2
d i g i t a l	PAGE 2 OF 3	
_ _ _ _		

Waivered Door Replacement

Early shipments of VAX 6000 series systems containing embedded storage had a waivered door shipped with the system. This old style door does not allow access to the embedded storage controls and indicators with out opening the cabinet door. These doors must be replaced with a new style door. The newer door allows access to embedded storage controls and indicators with out opening the cabinet door.

Procedures for replacing a door are included in this document.

WARNING

Care must be used in removing the new door from its shipping container. This container must be used to return the old door.

NOTE: This procedure is to be used only on waivered systems, NOT on field upgrades.

1. Inspect the packaging containing the new door for any obvious shipping damage. Ensure that any such damage is noted and reported thru normal channels.

- 2. Using care not to damage the packaging, unpack the new door from it's shipping container.
- 3. Remove and set aside the enclosed shipping tape and label.

 These will be used for packaging and shipping the old door.
- 4. Inspect the new door for any damage.
- 5. On the system, remove the door ground strap from the door only. This ground strap will be used on the new door therefore it is not necessary to remove the ground strap from the system frame.

NOTE: The door hinges contain a spring loaded pin that can be lifted up and turned to an unlocked position.

- 6. While supporting the door, lift and unlock both top and bottom door hinge pins. Set door aside.
- 7. On the new door, align and support the door while lifting and releasing the hinge pins into the hinges.

	FCO 63XMX-S002	
d i g i t a l	PAGE 3 OF 3	
_ _ _ _		

- 8. Reconnect the ground strap removed in step number four. Ensure the retaining nut is tightened securely.
- 9. Remove the door logo from the old door and reinstall it on the new door.
- 10. Close the front door and secure it with the hex key locks.
- 11. Place the old door in the shipping container. Tape the container closed in preparation for shipping.
- 12. Attach the shipping label to the outside of the container in a position where it will be plainly visible for the shipper to see.
- 13. US only contact your district CAS representative for an RA# (Return Authorization Number). CAS will need the DEC order number and customer name. CAS will arrange for pickup of this material.

Europe and GIA - follow local procedures for return of this material.

- 14. Update Site Management Guide to reflect this FCO.
- 15. Report FCO activity on LARS form in the "Module/fail area/FCO".

LARS

CATEGORY S	USA	GIA	EUROPE
Activity -			
(a)Contract and Warranty	W	U	Y
(b) IN-DEC Contract & Warranty	K		
Hardware Segment Code	111		
Non Contract/Non Warranty	F	F	F
(c)RTD/Off-site Agreement	F		
Product Line	01		

DEC Option	6000-3XX	6000-3XX	6000-3XX
Type of Call	M	M	M
Action Taken	D	D	I
Fail Area-Module-FCO-Comments	63XMX-S002	63XMX-S002	63XMX-S002
Material Used	EQ-01563-01	EQ-01563-01	EQ-01563-01

- (a) Warranty Optimum, Warranty Standard and Warranty Basic (on-site) Agreements.
- (b) Applies to INDEC AREA ONLY
- (c) RTD=Return to Digital or Off-site Agreements; If Field Engineer On-site, use Activity Code "F".

\^ 63XMX \\63XMX \\JACKSON \\1989 \\NOV

\\FCO_DOCS