



1- DIFFERENTIAL Z_o SHALL BE 105 ± 5 OHMS BETWEEN LEGS OF ANY DIFFERENTIAL PAIR.

2- MAXIMUM DIFFERENTIAL SKEW BETWEEN LEGS OF ANY DIFFERENTIAL PAIR IS RECOMMENDED TO BE LESS THAN 120 PSEC.

3- CROSSTALK: < 4%

4- MINIMUM EYE DIMENSIONS: HEIGHT: 316 mV, WIDTH: 300ps, JITTER: 100 ps.

5- MAXIMUM ASSEMBLY INSERTION LOSS: 10dB @ 1.25 GHz

6- LENGTH TOLERANCE: 5 METERS AND UNDER +4.0 INCHES/-0.0 INCHES

OVER 5 METERS +6.0 INCHES/-0.0 INCHES

7- CABLE EMI SHIELD SHALL BE TERMINATED TO BOTH CONNECTOR SHELLS.

8- CUSTOMER WILL SPECIFY LENGTH (IN METERS) BY INSERTING DESIRED LENGTH AS A DASH NUMBER AFTER THE IBN PART NUMBER WHEN ORDERING.

9- CONNECTOR PINOUT AND DETAIL ON PAGE 2.

GDRE		. GORE & ASSO Electronic Prov P.O. Box 160, Elkton, M © 2001 W. L. Gore	Maryland 21922-0160	By acceptance of this document you agree that all rights to drawings, specifications, processes and other data contained herein, as well as the proprieting varies one features of the subject matter, are rearred by Gore and are disclosed in confidence. They are not to be manufactured, used, sold of disclosed to others, nor are devices embodying such features or information diversel from these disclosed inclusions to the used or disclosed, while shard unit lengetedly autionized by Gore or information diversel from these discloses the used or disclosed, using shard unit lengetedly autionized by Gore. These diswings, specifications, processes, etc., are and remain the property of Gore and are not to be copied or englosed and the start of the copied or englosed and the start of the copied or englosed and the start of the copied or the start of the
Absense of a de	SSIFICATION KEY afect symbol from any es minor classification	DIMENSIONS ARE IN INCHES	UNLESS OTHERWISE SPECIFIED	Drawn ECL 08 OCT 2001 Check Approval
v c	Critical Feature	DO NOT SCALE DRAWING DEBURR SHARP EDGES	.XX ± N/A .XXX ± N/A .XXX ± N/A	Heat Treat N/A A
V M	lajor 1 Feature	$\oplus \bigcirc$.XXXX ± N/A FRACTIONS ± N/A	Title INFINIBAND 4X ASSEMBLY - IBN4000-L
V M	lajor 2 Feature	Third Angle Projection	ANGLES ± N/A SURFACE TEXTURE N/A	Dwg Size Sheet Scale Drawing Number C 1 of 2 1:1 Drawing Number
Pla Pla	ating Verification	INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5M-1994 (R1999)	BREAKS AND V FILLETS N/A MAX	Revision Rev Date Rev Description Rev Level 17 MAY 2005 DCN NO 05-068 H
4			3	2 1

	WIRING	CHART		
	END 1	END 2	2	
POS. #	ASSIGN	POS. #	ASSIGN	
G1-G8	SIGNAL GROUND	G1-G8	SIGNAL GROUND	
1	R+ (BIT 0)	16	T+ (BIT 0)	S2 — S16
2	R- (BIT 0)	15	T- (BIT 0)	
3	R+ (BIT 1)	14	T+ (BIT 1)	
4	R- (BIT 1)	13	T- (BIT 1)	
5	R+ (BIT 2)	12	T+ (BIT 2)	
6	R- (BIT 2)	11	T- (BIT 2)	
7	R+ (BIT 3)	10	T+ (BIT 3)	
8	R- (BIT 3)	9	T- (BIT 3)	
9	T- (BIT 3)	8	R- (BIT 3)	
10	T+ (BIT 3)	7	R+ (BIT 3)	I I I I I I I I I I I I I I I I I I I
11	T- (BIT 2)	6	R- (BIT 2)	$\mathbf{F}_{\mathbf{Y}}^{\mathbf{Y}} = \mathbf{Y}_{\mathbf{Y}}^{\mathbf{Y}} + \mathbf{F}_{\mathbf{Y}}^{\mathbf{Y}} + \mathbf{F}_{\mathbf$
12	T+ (BIT 2)	5	R+ (BIT 2)	
13	T- (BIT 1)	4	R- (BIT 1)	
14	T+ (BIT 1)	3	R+ (BIT 1)	
15	T- (BIT 0)	2	R- (BIT 0)	
16	T+ (BIT 0)	1	R+ (BIT 0)	G1 G9
DUSING	CHASSIS GROUND	HOUSING	CHASSIS GROUND	
				W. L. GORE & ASSOCIATES, INC. (Gore Electronic Products Division P.D. Box 160, Ethtor, Maryland 21922-0100 0.201 W. L. Gore & Associates, Inc.