SuperWorkstation 7034A-i Specifications

 Key Features 1. Dual Intel Xeon (Nocona) processor supported 2. Super × KDAL-G motherboard 3. Up to 12/24 GB ECC Reg. DDR333/266 SDRAM 4. Integrated Intel Gigabit Ethernet controller 5. 1/1 x16/x8 PCI-Express 6. 2 PCI-X-66MHz & 2 PCI 33MHz 7. 2 SATA connectors RAID 0, 1 supported 8. 6 channel surround sound 9. 1 floppy drive & 2 x 5.25" drive bays 10. 1 x 12cm PWM exhaust fan & 1 x 9cm PWM cooling fan 11. Suspend to RAM, Chassis intrusion 	
Processor/Cache	
Processor	Dual Intel® Xeon® processor with Extended Memory 64 Technology (EM64T)
Sysem Bus	800MHz
Key Applications	
	High-end workstation, business critical applications, front-end server, video server
Chipset/Serverboard	
	Intel® E7525/Super X6DAL-G
System Memory	
Memory Capacity	Six DIMM sockets for up to 24/12GB of ECC Reg. DDR333/266 SDRAM
Expansion Slots	
	1 x16 PCI-Express, 1 x8 PCI-Express, 2 64-bit PCI-X 66MHz, 2 32-bit PCI
SATA support	
	. 2 SATA connectors . RAID 0, 1 supported
Integrated On-Board	
LAN	Gigabit LAN with Intel® 82541PI Ethernet controllers
IDE	ATA/100 Hish suslits (channel ACI07 surlie
Audio Front Panel	High-quality 6-channel AC'97 audio
LED Indicators	Power status, HDD activity, one LAN link/activity, Fan fail/OH LED indication
Switches	Power switch, reset
Drive Bays	
Drive Bays	4x internal drive bays
Peripheral Bays	
. ,	1 floppy drive & 2 x 5.25" drive bays
Power Supply	Low noise fan speed control 645W power supply w/thermal control fan
Cooling System	
	1 x 12cm exhaust Pulse Width Modulated (PWM) fan & 1 x 9cm PWM cooling fan
Form Factor	Mid-tower Workstation
WxHxD	7" (178mm) x 16.69" (424mm) x 22" (559mm)
Weight	Gross: 45 lbs
0	

For the most current product information, visit: WWW.SuperMicro.com