SuperWorkstation 7044A-82 Specifications

Key Features

- 1. Dual Intel Xeon (Nocona) processor supported
- 2. Super X6DA8-G2 motherboard
- 3. Up to 16 GB ECC Reg. DDRII 400 SDRAM
- 4. Dual Intel Gigabit Ethernet controllers
- 5. 1 PCI-Express x16, 1 PCI-Express x4 (Dual x16 slots with one x16 and one x4 signal)
- 6. 1 PCI-X-133, 2 PCI-X-100, 1 PCI-33
- 7. Adaptec 7902 Ultra320 SCSI controller
- 8. Adaptec 2010S Zero channel RAID option
- 9. 8 x 1" hot -swap drive bays
- 10. IPMI 2.0 support
- **11.** 90-degree rotatable bays:
- 1 floppy drive & 2 x 5.25" drive bays
- **12.** 4 x 8cm hot-swap PWM cooling fans
- 13. Super-quiet 645W power supply with thermal control

Processor/Cache

| - | 10 | cc | 00 | U 1/ | ~ |
|---|----|-----|-----|-------------|---|
| | D | roc | 000 | 0.1 | |

Highest-end Xeon Workstation 800MHz System Bus with PCI-Express

Super Quiet & Tool-less Design



| 110ccssol/ Cacile | | | |
|---------------------|---|--|--|
| Processor | Dual Intel® Xeon® processor with Extended Memory 64 Technology (EM64T) | | |
| Sysem Bus | 800MHz | | |
| Key Applications | | | |
| | High-end workstation/server, business critical applications, front-end server, video server | | |
| Chipset/Serverboard | | | |
| | Intel® E7525/Super X6DA8-G2 | | |
| System Memory | | | |
| Memory Capacity | Eight DIMM sockets for up to 16GB of ECC Reg. DDRII 400 SDRAM | | |
| Expansion Slots | | | |
| | 1 x16 PCI-Express, 1 x4 PCI-Express (with x16 slot), 1 PCI-X-133, 2 PCI-X-100, 1 PCI-33 | | |
| SCSI/SATA | | | |
| | Adaptec 7902W dual channel Ultra320 SCSI host RAID controller with optional 2010S Zero channel RAID On-chip 2 SATA ports | | |
| Integrated On-Board | | | |
| LAN/Audio | Dual port Gigabit LAN with Intel® 82546GB Ethernet controller, High-quality 6-channel AC'97 audio | | |
| USB/IDE | Up to 4 USB 2.0 ports, ATA/100 | | |
| Front Panel | | | |
| LED/Switch | Power status, HDD activity, two LAN link/activity, fan fail/OH LED indication, power switch, reset switch | | |
| Drive Bays | | | |
| | 8 x 1" SCA drive bays with SAF-TE | | |
| Peripheral Bays | | | |
| | 90-degree rotatable drive bays for rackmount: 1 floppy drive & 2 x 5.25" drive bays | | |
| Management | | | |
| | SuperO Doctor III management software, Suspend to RAM, Watch Dog IPMI 2.0 support | | |
| Power Supply | | | |
| | Super-quiet 645W power supply with thermal control | | |
| Cooling System | | | |
| 8-9 | 4x 8cm hot-swap Pulse Width Modulated (PWM) cooling fans | | |
| Form Factor | 4U tower | | |
| Dimen./Weight | 7" (178mm) x 17.1" (434mm) x 24.4" (620mm), 53lb. gross weight | | |
| Optional Kits | Rail Kit: CSE-PT26 | | |

For the most current product information, visit: WWW.SUPERMICRO.COM

2003 Super Micro Computer Inc. Specifications subject to change without notice. All other brands and names are the property of their respective owners ©