



Contents

Main Unit	260x220x57.7 mm (hxwxd), approx 3 kg with UV protected, IP 66 Aluminum die cast casing
1 Wireless Handset	138x54x25.6 mm (hxwxd), with UV protected, IP 66 casing
1 Handset Cradle	137x74x42.5 mm (hxwxd) handset holder and charging base
1 Universal AC/DC Power Supply	12V, 3A, waterproof, with three-pin heads
1 USB Cable	1 m waterproof
1 RJ-11 Cable	2 m waterproof
Utility CD	Unit management software USB Driver User manual
User Manual	English
Warranty Card	English
Antenna	Active omni-directional antenna or Stabilized marine antenna

Technical Specifications

Interfaces	<ul style="list-style-type: none"> 1 x RJ11: <ul style="list-style-type: none"> - Extension phone (Voice call) - Extension G3 FAX machine (Fax call) 1 x USB: <ul style="list-style-type: none"> - PC connection (GmPRS, Data & Fax call) 1 x DTE (9 Pin): <ul style="list-style-type: none"> - PC connection (GmPRS, Data & Fax call) 1 x I/O: <ul style="list-style-type: none"> - External emergency button 1 x TNC: <ul style="list-style-type: none"> - Satellite antenna connection 1 x SMA: <ul style="list-style-type: none"> - GPS antenna connection
Displays	<ul style="list-style-type: none"> Main Unit LCD: Displays call status Handset LCD: Displays call status POWER LED: Displays power on/off status
Power	<ul style="list-style-type: none"> Universal AC/DC power supply: 110 ~ 240V, 3A, free voltage input Terminal Input power DC 12V/24V/34V (waterproof)
User interface	PC based Management software connected to the main unit, LCD and keys on the handset