

Wireless LAN





Power Over Ethernet Adapter

The DWL-P200 Power Over Ethernet (PoE) adapter is designed to supply operational power to surveillance cameras and wireless LAN devices such as access points, bridges and routers. It enable power current to travel on the Ethernet network cable, thus eliminates the need to directly connect a power supply to the wireless LAN device. The DWL-P200 supports both 5VDC and 12VDC power requirements. Power requirement can be selected through a DIP switch.

Facilitates Installation

The Power Over Ethernet allows you to install the wireless LAN device and surveillance camera at places such as on a building rooftop, on or near a ceiling, or other difficult places where power is not easily accessible. The idea is increase the usefulness of your camera and wireless LAN to provide connectivity to users regardless of their proximity to a power outlet or a network cable.

Data and DC Power Transmission on the Same Network Cable

On a standard UTP Category 5 cable, only two pairs (pins 1, 2, 3 and 6) are used for Ethernet data transfer. Power Over Ethernet is designed to take advantage of the unused pins of

the remaining pair of cable wires. Consequently, a single Category 5 cable will now carry both Ethernet data and DC power. The idea is to supply the remote end with power and the requirements of Ethernet connectivity via a single Cat 5 cable.

Base Unit and Terminal Unit

The DWL-P200 includes a base unit and a terminal unit. At one end, the base unit inserts DC voltage into the unused wires (pins 4, 5, 7 and 8) of the network cable. At the other end, the terminal unit splits the data and DC power apart. Data signals continue to travel on remaining network cables, while DC power is fed into the power adapter, which connects to an AC power outlet.

Key Features

- Provides DC power over existing Category 5 cable to wireless LAN device
- Cuts costs and provides convenience
- Transforms incoming AC power into low-voltage DC power
- 1 base unit and terminal unit provide power to 1 wireless LAN device
- Protects wireless LAN device from possible power-surges
- Supports both 5VDC and 12VDC power (selectable through a DIP switch)

DWL-P200 **Technical Specifications**

Power Over Ethernet Includes

- 1 base unit
- 1 terminal unit

Category 5 Pin Power Usage

- Data: pins 1, 2, 3, 6 - Power: pins 4, 5, 7, 8

Output Voltage

- Input: 48VDC, 400mA - Output: 5VDC or 12VDC (DIP switch selectable)

Ethernet Cable

- Data rate: 10/100Mbps
- TIA/EIA 568 Cat. 5
- Connector: RJ-45

Dimensions

- Base unit: 81 x 52 x 28 mm
- Terminal unit: 81 x 52 x 28 mm

Operating Temperature 0° to 40° C

Storage Temperature -40° to 70 °C

Operating Humidity 10% to 80% RH

Storage Humidity 5% to 90% RH

EMI Certification

- FCC Part 15 Class B - CE Class B

Power Adapter Safety Certifications CSA International

Box Includes

- Power Over Ethernet base unit
- Power Over Ethernet terminal unit
- AC to DC power adapter
- DC power cable
- Quick Installation Guide
- Ethernet cable

FCCE **Ordering Information**

DWL-P200

Power Over Ethernet

Please specify your order as follows:

DWL-P200/A DWL-P200/B **DWL-P200/E DWL-P200/N** DWL-P200/CN US standard power adapter UK standard power adapter EU standard power adapter Australia standard power adapter China standard power adapter

link

subject to change Link is a registered trademarks of Link Corporation/D-Link System Inc

> France Netherlands Belgium Italy Iberia Sweden Norway Denmark Finland Singapore Australia Turkey Egypt Israel Latinamerica Brasil South Africa Russia Taiwan

U.S.A

Canada Europe Germany

TEL: 1-714-885-6000 TEL: 1-905-8295033 TEL: 44-20-8731-5555 TEL: 49-6196-77990 TEL: 33-1-30238688 TEL: 31-10-282-1445 TEL: 32(0)2-517-7111 TEL: 39-2-2900-0676 TEL: 34-93-4090770 TEL: 46-(0)8564-61900 TEL: 47-22-309075 TEL: 45-43-969040 TEL: 358-9-2707-5080 TEL: 65-6774-6233 TEL: 61-2-8899-1800 TEL: 81-3-5434-9678
 Japan
 TEL: 81-3-5434-9674

 China
 TEL: 86-10-8518-25

 India
 TEL: 91-022-652-66

 Middle East (Dubai) TEL: 9714-8834234
TEL: 86-10-8518-2533 TEL: 91-022-652-6696 TEL: 90-212-335-2553 TEL: 202-414-4295 TEL: 972-9-9715700 TEL: 56-2-232-3185 TEL: 55-11-55039320 TEL: 27(0)1266-52165 TEL: 7-095-744-0099 TEL: 886-2-2910-2626 TEL: 886-2-2916-1600

FAX: 1-905-8295223 FAX: 44-20-8731-5511 FAX: 49-6196-7799300 FAX: 33-1-30238689 FAX: 31-10-282-1331 FAX: 32(0)2-517-6500 FAX: 39-2-2900-1723 FAX: 34-93-4910795 FAX: 46-(0)8564-61901 FAX: 47-22-309085 FAX: 45-43-424347 FAX: 358-9-2707-5081 FAX: 65-6774-6322 FAX: 61-2-8899-1868 FAX: 81-3-5434-9868 FAX: 86-10-8518-2250 FAX: 91-022-652-8914 FAX: 9714-8834394 FAX: 90-212-335-2500 FAX: 202-415-6704 FAX: 972-9-9715601 FAX: 56-2-232-0923 FAX: 55-11-55039321 FAX: 270)1266-52186 FAX: 7-095-744-0099#350 FAX: 886-2-2910-1515 FAX: 886-2-2914-6299

FAX: 1-866-743-4905

Wireless LAN



D-Link Corp.