



- **Superior performance for high-bandwidth applications**
 - 8.0 Gbps switching fabric and wire-speed, standards-based IP/IPX routing
 - Expansion modules provide increased Gigabit Ethernet uplinks as well as Serial WAN and Fast Ethernet connectivity
- **Pinpoint application control**
 - Wire-speed Layer 4 application control enables prioritization of business-critical information without performance degradation
- **Extensive security**
 - Maximum workgroup security obtained with Access Control Lists and up to 2000 security filters applied at Layer 2, 3 or 4
- **Low cost of ownership**
 - Low module cost and seamless integration with Matrix E6 and E7 chassis/switching modules ensure cost-effective implementation
- **Industry-leading management for definition and enforcement of service level agreements**
 - NAT and DHCP capabilities allow flexible user adds, moves and changes
 - Supports full RMON I and II
 - Supports CoreWatch Java-based device manager and full SNMP management via NetSight™

Meet the Demands of High-Bandwidth Applications

Integrate the features and functionality of the award-winning X-Pedition switch router into the wiring closet.

High-Density, Wire-Speed Switching and Routing for the Enterprise Wiring Closet

Enterasys offers IT professionals a full range of switching and routing solutions for the wiring closet. The Matrix 6SSRM-02 Advanced Router Module brings all of the functionality of the award-winning X-Pedition™ switch router to the industry-leading Matrix E6 and E7 for high-density, wire-speed switching and routing in the wiring closet.

The Advanced Router Module can be used to route between modules or VLANs within a Matrix E6 or E7 chassis, and is ideal for customers requiring multiple autonomous workgroups at the wiring closet. Extending the Matrix's unique, built-in protocol and application control, the Advanced Router Module adds IP/IPX routing, ACLs, RMON II, NAT support, DHCP capability and enhanced multicast support.

The module protects customers' investments by providing a simple implementation path without sacrificing existing equipment. In addition, the module and per-port costs of the Advanced Router Module are lower than competitive solutions.

The Advanced Router Module can also provide up to four routed Gigabit uplinks to the network backbone. Two expansion module slots allow for a variety of connectivity options, including 10/100Base-TX, 100Base-FX, 1000Base-SX/LX/LLX, and serial WAN.



TECHNICAL SPECIFICATIONS

Capacity

Up to 16,000 routes, 128,000 Layer 4 application flows, 180,000 Layer 2 MAC Addresses, and 2,000 security/access control filters; 4,096 VLANs, 3 MB buffering per Gigabit port, 1 MB buffering per 10/100 port

Performance

8.0 Gbps non-blocking switching fabric, 6.0 Mpps routing throughput

PHYSICAL SPECIFICATIONS

Dimensions

41.91 cm (16.5") H x 6.1 cm (2.4") W x 32.5 cm (12.8") D

Weight

2.6 kg (5.9 lbs)

In-Band Management

Remote SNMP via CoreWatch and NetSight

Out-of-Band Management

RS-232 and Telnet

MTBF (predicted)

> 200,000 hours

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature

41° to 104° F (+5° to +40° C)

Non-Operating Temperature

-22° to 164° F (-30° to +73° C)

Operating Humidity

15% to 90% (non-condensing)

Power Consumption

100 to 125 VAC, 2A max or 200 to 250 VAC, 1A max; 60 Hz

AGENCY AND STANDARDS SPECIFICATIONS

Safety

Meets the requirements of UL1950, CSA C22.2 No. 950, EN60950, IEC950 and 72/73/EEC

Electromagnetic Compatibility

Compliant with the requirements of FCC Part 15, CSAC108.8, EN555022, VCCI V-3/93.01, EN50082-1 and 89/336/EEC

RFCs/MIBs

RFC 1213 - MIB-2; RFC 1493 - Bridge MIB; RFC 1573 - Interfaces MIB; RFC 1643 - Ethernet-like interface MIB; RFC 1163 - BGP; RFC 1267 - BGP-3; RFC 1771 - BGP-4; RFC 1657 - BG-4 MIB; RFC 1058 - RIP v1; RFC 1723 - RIP v2; RFC 1724 - RIP v2 MIB; RFC 1757 - RMON; RFC 1583 - OSPF Version 2; RFC 1253 - OSPF v2 MIB; RFC 2096 - IP Forwarding MIB; RFC 1812 - Router Requirements; RFC 1519 - CIDR; RFC 1157 - SNMP; RFC 2021 - RMON2; RFC 2068 - HTTP

Standards

IP Routing: RIPv1/v2, OSPF, BGP-4; IPX Routing: RIP, SAP; Multicast Support: IGMP, DVMRP, PIM (Future); IEEE 802.1p; IEEE 802.1Q; IEEE 802.1d Spanning Tree; IEEE 802.3; IEEE 802.3u; IEEE 802.3x; IEEE 802.3z

ORDERING INFORMATION

6SSRM-02

Advanced Router Module for the Matrix E6 and E7

Expansion Modules

6SSRLC-TX-AA

8-port 10/100Base-TX

6SSRLC-FX-AA

8-port 100Base-FX (MTRJ)

6SSRLC-SX-AA

2-port 1000Base-SX

6SSRLC-LX-AA

2-port 1000Base-LX

6SSRLC-LX70-AA

1-port 1000Base-LX 70 KM

6SSRLC-SER-AA

2-port Serial

6SSRLC-SERC-AA

4-port Serial w/compression

6SSRLC-SERCE-AA

4-port Serial w/compression + encryption

Matrix, X-Pedition and NetSight are trademarks or registered trademarks of Enterasys Networks, a Cabletron Systems Company. All other products or services mentioned are identified by the trademarks or service marks of their respective companies or organizations. NOTE: Enterasys Networks reserves the right to change specifications without notice. Please contact your representative to confirm current specifications.