



X-Pedition™ ER16-OS26-01 10-Gigabit Ethernet Module

- Provides 10-Gigabit Ethernet connectivity
- Enables QoS, bandwidth provisioning and advanced security
- Assures the performance of bandwidth-hungry applications like audio/video multicasting, Internet telephony and interactive transaction processing

- **High-performance 10-Gigabit Ethernet**

- 2-slot line card for one modular port of IEEE 802.3ae 10-Gigabit Ethernet connectivity
- Uses IEEE 802.3ae compliant SC duplex fiber optic connectors; provides one port of 1310nm Serial SMF connectivity enabling drive distances of between 2 Km and 10 Km

- **QoS for traffic control across the enterprise**

- Allocate bandwidth to users on a per-port basis
- Assign traffic to queues based on application, user, or incoming priority-tagged packets
- Select Strict Priority or Weighted Fair Queuing on a per-port basis
- Supports policy-based routing

- **100% availability features**

- Supports 802.3ad link aggregation
- Supports VRRP, Equal Cost Multi-Path OSPF, and LS NAT
- Premiere Load Balancing for 100% availability
- Supports hot swappable, redundant power supplies

- **Security without performance degradation**

- ACLs and traffic filters at Layer 2, 3, or 4 without compromising performance
- Management authorization/authentication via RADIUS

Powerful 10-Gigabit Ethernet for Mission-Critical Networks

The X-Pedition ER16-OS26-01 10-Gigabit Ethernet Module for the X-Pedition ER16 supports true core routing at 10-Gigabit Ethernet rates and enables services such as advanced Quality of Service, bandwidth provisioning, and advanced security.

The X-Pedition ER16-OS26-01's two-slot line card offers one modular port of IEEE 802.3ae standards-based 10-Gigabit Ethernet connectivity, for up to seven 10-Gigabit Ethernet ports in a single ER16 chassis. Media support is provided via modular 10GBASE interface modules. These optical interfaces are based on IEEE 802.3ae-compliant SC duplex fiber optic connectors. The first available interface is the 10GBASE-LR, which

provides one port of 1310nm Serial SMF connectivity and enables drive distances of between 2 Km and 10 Km. Future interface modules will support 850nm Serial MMF, 1310nm 4 Channel WDM and 1550nm Serial SMF.

The availability of 10-Gigabit Ethernet, combined with the X-Pedition's Quality of Service features, means that organizations can assure the performance of bandwidth-hungry applications like real-time audio/video multicasting, Internet telephony, and interactive transaction processing. Organizations can also extend their infrastructure into the MAN and WAN, offering the same level of performance, security, capacity, and control to all enterprise users, regardless of application used or the user's location.

Specifications

TECHNICAL Specifications

MTBF

>175,000 hr /> 19 years

In-Band Management

Remote SNMP via NetSight™ Atlas

Physical Specifications

Dimensions

47.75 cm (18.80") H x 36.45 cm (14.35") D x 3.94 cm (1.55") W

Weight

4.52 kg (9 lbs, 15 oz)

Environmental Specifications

Operating Temperature

0° C to +40° C (32° F to 104° F)

Non-Operating Temperature

-40° C to +73° C (-40° C to 164° F)

Operating Humidity

10% to 90% (non-condensing)

Power Consumption

140 watts

Agency And Standards Specifications

Safety

UL 60950, CSA 60950, EN 60950, EN 60825 and IEC 60950

Electromagnetic Compatibility

47 CFR Parts 2 and 15, CSA C108.8, EN 555022, EN 55024, EN 61000-3-2, EN 61000-3-3, AS/NZS CISPR 22, and VCCI V-3

IP Routing

RIPv1/v2, OSPF, BGP-4

IPX Routing

RIP, SAP

Multicast

IGMP, DVMRP, PIM-SM

QoS

Application level, 802.1p

RFCs/MIBs

IEEE 802.1p—Traffic Prioritization

IEEE 802.1Q—VLAN Trunking

IEEE 802.1D—Spanning Tree

IEEE 802.1w—Rapid Spanning Tree

IEEE 802.3—10 Mbps Ethernet

IEEE 802.3ae—10GbE

IEEE 802.3u—100Base-T Ethernet

IEEE 802.3x—Full Duplex Ethernet

IEEE 802.3z—1000 Mbps Ethernet

RFC 1213—MIB-2

RFC 1493—Bridge MIB

RFC 1643—Ethernet-like Interface MIB

RFC 1771—BGP-4

RFC 1657—BGP-4 MIB

RFC 1058—RIP v1

RFC 1723—RIP v2

RFC 1724—RIP v2 MIB

RFC 1583—OSPF v2

RFC 1850—OSPF v2 MIB

RFC 1812—Router Requirements

RFC 2096—IP Forwarding MIB

RFC 1349—Type of Service in the IP Suite

RFC 1519—CIDR

RFC 2338—VRRP

RFC 2391—LSNAT

RFC 2618—Radius-Auth-Client-MIB

RFC 2737—Entity MIB

RFC 2790—Host Resource MIB

RFC 1157—SNMP

RFC 2819—RMON 1

RFC 2021—RMON 2

RFC 1332—PPP IP Control Protocol (IPCP)

RFC 1548—The Point-to-Point Protocol (PPP)

RFC 1552—PPP IPX Control Protocol (IPXCP)

RFC 1570—PPP LCP Extensions

RFC 1717—PPP Multilink Protocol

RFC 1662—PPP in HDLC-like Framing

RFC 1661—PPP (Point-to-Point Protocol)

RFC 1638—PPP Bridging Control Protocol

RFC 1293—Inverse ARP

RFC 1315—MIB for Frame Relay DTEs

RFC 1490—Multiprotocol Interconnect over FR

Frame Relay Forum and ITU Standards

FRF.1.1, FRF.3.1, Q.922/ANSI T1.618, Q.933,

I.122/ANSI T1S1 Annex D/ANSI T1.617

Ordering Information

ER16-OS26-01

Dual-slot 10-Gigabit Ethernet switch routing module for the X-Pedition ER16; single port configuration, accepts physical modules for connectivity

10GBASE-LR

1-port 1310nm Serial single-mode fiber interface for the ER16-OS26-01

Warranty

As a customer-centric company, Enterasys is committed to providing the best possible workmanship and design in our product set. In the event that one of our products fails due to a defect in one of these factors, we have developed a comprehensive warranty that protects you and provides a simple way to get your products repaired as soon as possible.

Service and Support

Enterasys understands that superior service and support is a critical component of *Networks that Know*.™ The Enterasys **SupportNet Portfolio**—a suite of innovative and flexible service and support offerings—completes the Enterasys solution. SupportNet offers all the post-implementation support services you need—online, onsite or over the phone—to maintain your network availability and performance.

Additional Information

For additional information on the X-Pedition, visit enterasys.com/products/routing

Contact Information

Contact Enterasys Sales at **877-801-7082** or enterasys.com/corporate/contact/contact-sales.html

Enterasys Networks
Corporate Headquarters
50 Minuteman Road
Andover, MA 01810
U.S.A

X-Pedition is a trademark or registered trademark of Enterasys Networks. All other products or services mentioned are identified by the trademarks or service marks of their respective companies or organizations. NOTE: Enterasys Networks reserves the right to change specifications without notice. Please contact your representative to confirm current specifications.

All contents are copyright © 2004 Enterasys Networks, Inc. All rights reserved.

Lit. #9013136-1 4/04

Page 4 of 4 • Data Sheet

