

ioDrive Octal



- > Sustain over 1 Million I/Os per second
- > Achieve latency as low as 30 μ s
- > Managed like simple block storage

WWW.FUSIONIO.COM

ioDrive Octal Capacity		5.12TB
NAND Type	MLC (Multi Level Cell)	
Read IOPS (512 B)	1,190,000	
Write IOPS (512 B)	1,180,000	
75/25 Mix IOPS (512 B)	729,000	
Read Bandwidth (64 kB)	6.0 GB/s	
Write Bandwidth (64 kB)	4.4 GB/s	
Access Latency (512 Byte)	30 μ s	
Bus Interface	PCI-Express x16 Gen2.0	
Operating Systems	64-Bit Microsoft Server 2003/2008, 64-Bit Microsoft Windows XP/Vista/Win7, RHEL 4/5/6, SLES 10/11, OEL v4/v5, VMware ESX 4.0/4.1	

AGENCY

US / Canada	ANSI C63.4/EN 55022/ CNS 13438, Radiated and Conducted Emissions Class A EN 55024 Immunity EN 55022 Class A
Europe	2004/108/EC EMC Directive CE IEC 61000 Class A Mark
Japan	VCCI - V-2/2009.04
Taiwan	BSMI - CNS 13438 / EN 55022 class A
New Zealand/Australia	AS/NZS CISPR22:2006 / 47CFR Part 15, Radiated and Conducted Emissions Class A
Korea	KCC - FIO-IODRIVE (Class A)
RoHS	RoHS - EU Directive 2002/95/EC


STANDARDS

Form Factor	PCI Express x16 Gen 2.0 Double Wide
Connectivity	PCI Express electromechanical spec 2.0
Power	PCI Express power spec 2.0
Max Power Consumption	150w
Required Power Connections	(1) 8-Pin PCIe 150w connector or (2) 6-Pin PCIe 75w connectors

ENVIRONMENTAL SPECIFICATIONS

		Min	Max
Temperature (C)*	Operational	0	55
	Non-operational	-40	70
Air Flow (LFM)		300	
Humidity (%)	Non-condensing	5	95
Altitude	Operational		10,000
	Non-operational		30,000

* Temperature derated 1 C per 1000 ft elevation above sea level
100% Designed and Assembled in the U.S.A.



FUSION-io®