

# Hitachi TagmaStore™ Adaptable Modular Storage Model AMS200

For small and medium-sized businesses, model AMS200 offers a highly scalable, reliable, and cost-effective platform for Microsoft Exchange Server and other business applications, tiered storage, consolidation, first SAN deployment, backup, or data archiving.

## Enterprise-class Solutions for SMB Customers

Small and medium-sized businesses (SMBs) are facing big-company challenges of escalating data growth, availability, and protection as well as regulatory compliance and complex storage infrastructures. With many years of experience serving Fortune 500 companies, Hitachi Data Systems understands these challenges and has developed Application Optimized Storage™ solutions to match application requirements to storage attributes. Now Hitachi Data Systems brings SMB customers these proven solutions in modular, cost-effective packaging, including the Hitachi TagmaStore™ Adaptable Modular Storage model AMS200.

## Business Benefits

### Manage storage costs while ensuring scalability, reliability, and flexibility

- Move from server-internal storage to scalable external storage, consolidate multiple storage systems into one, or build a first storage area network (SAN).
- Match the value of your data to the cost of storage with a system that supports native Fibre Channel SAN and cost-effective Serial ATA (SATA) intermix drives.
- Scale to 40.5TB of SATA and Fibre Channel storage (intermix) to keep up with data growth.
- Support very large numbers of servers and applications with 512 LUNs.

- Benefit from easy-to-use software utilities for configuration and management.
- Use advanced features, Cache Partition Manager and RAID-6, to help improve performance, reliability, and usability.
- Partition and dedicate cache to maximise performance of high-I/O applications.

### Protect critical data

- Enhanced SATA data protection for unmatched data availability and resiliency
- RAID-6 for high availability and rapid RAID group rebuild times
- Hi-Track® “call-home” service/remote maintenance tool for 24/7 diagnostics to keep potential issues from becoming problems
- Fully redundant and hot-swappable components to keep applications online
- Within-system volume replication or incremental copies for frequent backups

### Build a first storage network or extend an existing one

- Simple SAN and SAN Starter solutions for easy deployment
- Diskless boot for SAN-attached servers
- High-capacity storage for network attached storage (NAS) applications
- Manage and configure your systems using Hitachi HiCommand® Suite and Storage Area Management (SAM) software.

## Modular Storage for the Midrange Market

- Hitachi TagmaStore™ Network Storage Controller
- Hitachi Thunder 9585V™ ultra high-end modular storage
- Hitachi TagmaStore™ Adaptable Modular Storage model AMS500
- Hitachi TagmaStore™ Adaptable Modular Storage model AMS200
- Hitachi TagmaStore™ Workgroup Modular Storage model WMS100

## Leverage for SMB applications or enterprise tiered storage deployments

- Microsoft Exchange Server, ERP, CRM, database, NAS filer, backup applications, or tape replacement

- Archival and long-term tamperproof data retention to meet regulatory requirements
- Combine with Hitachi enterprise-class storage for complete data lifecycle management solutions within a tiered storage environment.

## Adaptable Modular Storage - Model AMS200 Specifications

### Physical Characteristics

Raw capacity	40.5TB SATA Intermix 31.5TB Fibre Channel
Disk drive technology options - Fibre Channel unless otherwise noted	73GB (10,000RPM) 73GB (15,000RPM) 146GB (10,000RPM) 300GB (10,000RPM) 250GB SATA (7200RPM) 400GB SATA (7200RPM)
Disk drive interface	SATA-Fibre Channel Intermix
Minimum/maximum number of disk drives	5-105 Fibre Channel 0-90 SATA
Model upgrade options	AMS500
Number of controllers	1 or 2
Host Fibre Channel connections	4 at 1Gbit/sec or 2Gbit/sec
Maximum attached hosts (virtual ports)	512
Active loops per number of disk drives	4/15
LUNs	512

### RAID Support

- RAID-0 (Fibre Channel only)
- RAID-1
- RAID-0+1
- RAID-5
- RAID-6

### Availability

Nondisruptive component replacement	MAJOR FRU
Nondisruptive hot-pluggable disks	
Nondisruptive microcode updates	
Hi-Track® "call-home" service/remote maintenance tool	

### Performance

Maximum cache	2GB-4GB
Cache binding	Hitachi Cache Residency Manager feature
Cache partitioning	

### Software

Management software	Hitachi Resource Manager™ utility package, Hitachi HiCommand® Suite and Storage Area Management (SAM)
Common APIs	YES - across Hitachi storage systems
Remote copy	N/A
Point-in-time copy	Hitachi ShadowImage™ In-System Replication, Hitachi Copy-on-Write Snapshot
Serverless disk copy and tape	Hitachi Cross-System Copy to/from Hitachi TagmaStore™ Universal Storage Platform and Hitachi Lighting 9900™ V Series systems
LU-change-ownership	
LUN security	Hitachi Volume Security
Host Storage Domains virtual private storage Multiple LUN0/port	
Storage system-based "write once, read many" (WORM) data protection	Hitachi Data Retention Utility
Dynamic LUN management	Logical Volume Concatenation
Host failover	Hitachi Dynamic Link Manager™ path manager
Heterogeneous SAN management	HiCommand Storage Services Manager and HiCommand Path Provisioning Manager, both powered by ApplIQ

### Operating Systems Support

- IBM® AIX®
- HP-UX
- Sun Solaris
- Microsoft Windows NT, Windows 2000, Windows Server 2003
- HP Tru64 UNIX
- SGI IRIX
- Novell NetWare
- LINUX
- HP OpenVMS
- NetApp® Data ONTAP, via HDS-NetApp Enterprise NAS Gateway
- IBM z/OS®, via Universal Storage Platform external attachment
- VMWare
- Apple MAC OS

Note: All capacities are based on 1GB = 1,000,000,000 bytes; 1TB = 1000GB

## Hitachi Data Systems Corporation

### European Headquarters Hitachi Data Systems

Sefton Park  
Stoke Poges  
Buckinghamshire SL2 4HD  
Phone: +44 (0) 1753 618000  
Fax: +44 (0) 1753 618550  
[info.eu@hds.com](mailto:info.eu@hds.com)  
[www.hds.com](http://www.hds.com)

Hitachi Data Systems is registered with the U.S. Patent and Trademark Office as a trademark and service mark of Hitachi, Ltd. The Hitachi Data Systems logotype is a trademark and service mark of Hitachi, Ltd. HiCommand is a registered trademark of Hitachi, Ltd.

Hi-Track is a registered trademark and Application Optimized Storage, TagmaStore, Resource Manager, ShadowImage, Lightning 9900, Thunder 9500, and Dynamic Link Manager are trademarks of Hitachi Data Systems Corporation.

All other product and company names are, or may be, trademarks or service marks of their respective owners.

Notice: This document is for informational purposes only, and does not set forth any warranty, express or implied, concerning any equipment or service offered or to be offered by Hitachi Data Systems. This document describes some capabilities that are conditioned on a maintenance contract with Hitachi Data Systems being in effect, and that may be configuration-dependent, and features that may not be currently available. Contact your local Hitachi Data Systems sales office for information on feature and product availability.

Hitachi Data Systems sells and licenses its products subject to certain terms and conditions, including limited warranties. To see a copy of these terms and conditions prior to purchase or license, please go to [http://www.hds.com/products\\_services/support/warranty.html](http://www.hds.com/products_services/support/warranty.html) or call your local sales representative to obtain a printed copy. If you purchase or license the product, you are deemed to have accepted these terms and conditions.

©2005, Hitachi Data Systems Corporation. All Rights Reserved.  
DISK-549-00-EU June 2005