



GlobeTrotter **GT MAX HSUPA**

- Wireless DSL-like speed: downloads up to 7.2 Mbps, uploads up to 2 Mbps
- Ultra compact design with patented retractable antenna
- Worldwide connectivity by Multi-standard (HSUPA, HSDPA, UMTS, EDGE and GPRS) and Multi-band support
- Faster and more stable connectivity with two antennas and Advanced Receiver Technology
- Plug 'n Play through Zero-CD™ technology



About GlobeTrotter **GT MAX HSUPA** (Models: GX 301 / GX 302)

The GlobeTrotter GT MAX HSUPA gives you the latest technology with Option's proven performance and reliability in a very compact format. Within the GlobeTrotter GT MAX HSUPA we provide a multi-band, multi-technology transceiver offering the best upload and download speeds available today. HSPA (HSDPA and HSUPA combined) is an essential technology for today's and tomorrow's enlarged media environment.

The GlobeTrotter GT MAX HSUPA is designed to achieve peak HSDPA download speeds of 7.2 Mbps with HSUPA uploads approaching 2 Mbps. Backward compatibility ensures HSDPA connections at lower data rates of 3.6 Mbps and 1.8 Mbps with upload speeds to 384 Kbps. The wireless data card also has inherent support for UMTS operation at 384 Kbps in conjunction

with quad-band EDGE and GPRS. The Advanced Receiver Technology (ART) within GlobeTrotter GT MAX HSUPA gives the benefit of Receive Diversity and Receive Equalization. Both are essential for maximizing the benefit of HSDPA 7.2. The design of the GlobeTrotter GT MAX incorporates Option's unique and patented 'Butterfly' retractable antenna concept that frees you from the need to remove any part of your card from your notebook for transport.

The GlobeTrotter GT MAX HSUPA uses Option's Zero-CD™ technology. Applications, manuals and drivers are distributed and installed automatically when the GlobeTrotter GT MAX HSUPA is inserted for the first time. There is no need for CD installation or bulky printed book; GlobeTrotter GT MAX HSUPA is a truly unique Plug 'n Play solution.

Features

- Worldwide coverage through triple-band HSUPA/HSDPA/UMTS, quad-band EDGE/GSM
- Multimode HSUPA/HSDPA/UMTS/EDGE/GPRS/GSM card
- Advanced Receiver Technology incorporating Receiver Diversity and Equalization
- Zero-CD™ Plug 'n Play technology
- HSUPA upload (up to 2 Mbps), HSDPA and UMTS download (up to 7.2 Mbps)
- Provides EDGE/GPRS/GSM data (up to 247 Kbps) connectivity
- Transparent hand-over between UMTS and GSM/EDGE networks
- Compatible with nearly all popular notebook PC's equipped with a Cardbus card slot
- Securely access corporate resources with its transparent support for IPSec and VPN technology
- PCSC-driver for EAP-SIM and other 3-party applications in need of a Smart Card Interface
- Supports third party applications that provide Video Telephony (3GPP 3G-324M, H.324, H264 Baseline Video), SIP, SMS, IM, MMS, Internet and e-mail
- Comprehensively tested on infrastructures and networks worldwide
- Future proofing through Flash Memory technology



Specifications

- HSUPA/HSDPA/UMTS Air Interface:
 - WCDMA 850 / 1900 / 2100 MHz
 - 3GPP FDD compliant, up to 7.2 Mbps Peak Rate
 - UE Power Class 3
 - HSUPA Category 5
 - High Speed packet-switched data:
 - Support for UMTS QoS traffic classes
 - Support for PPP, IP transparent and non-transparent modes
 - Circuit-switched data Single-RAB streaming: 64, 57.6, 28.8 and 14.4 Kbps
 - Dual antenna Receiver Diversity
 - GX 301: EMEA variant supporting diversity on 2100 MHz
 - GX 302: World variant supporting diversity on 850 and 1900 MHz
 - Receiver Equalization
- EDGE/GSM Air Interface:
 - 850/900/1800/1900 MHz
 - EDGE Power Class E2, GSM Power Class 1 at 1800/1900 MHz and Power Class 4 at 850/900 MHz; coding scheme UL & DL – CS 1-4, MCS 1-9
- Packet-switched data:
 - Multislot (E)GPRS Class 12, (E)GPRS Class B Type 1 MT
 - Streaming, Background and Interactive QoS Classes Supported
- Circuit-switched data: 14.4, 12.2 and 9.6 Kbps
- Terminal Equipment Interfaces:
 - Drivers: Windows™ 2000 Pro, Personal and XP Pro/Home, Vista and MAC OS X
 - A PCSC compatible driver, compliant with ISO 7816 and 3GPP TS11.11
 - SIM-ME interface as specified in 3GPP GSM TS11.11 and GSM 11.12 and with compliance to ISO 7816
 - SIM Application toolkit capable SIM to 3GPP GSM TS11.14
 - NDIS or Standard modem emulation for compatibility with terminal programs/dialers and for use with proprietary operating systems AT Interface 3GPP TS27.005, ATD*99# and ATD*99***<CID># support
 - Multiple communication ports for simultaneous data call and network coverage reports

Hardware specifications

- Card Type: Cardbus
- Miniature External Antenna Connection
- Red LED for GSM/GPRS/EDGE and blue LED for HSUPA/HSDPA/UMTS
- SIM card interface compliant with 3GPP 31.101 and 31.102 supporting 1.8 and 3V UICCs
- Environmental Operating temperature: 0 to + 55°C

Approvals/certifications

- All applicable regulatory approvals, Operator and Infrastructure IOT
- Microsoft WHQL certified drivers
- RoHS Compliant



As part of their continual product improvement process, Option reserves the right to alter the specifications for the product detailed here. "GlobeTrotter GT MAX" and "GlobeTrotter Connect" are registered trademarks of Option. The Apple logo, Mac and Mac OS are trademarks of Apple Computer, Inc.